

#### HOW TO SELECT A TYRE

- Consult Vehicle Owner's Manual or Door
- Placard for Proper Tyre Size and Load/Speed Index
- Consider Average Vehicle Usage (Extended Highway Use, Off-Road, etc.)

#### MOUNTING/DISMOUNTING/SERVICE:

- Only Allow Trained Professionals to Mount, Dismount, or Service Your Tyres.

#### TYRE PRESSURE

- Consult Vehicle Owner's Manual or Door Placard for Proper Pressure for Your Vehicle. PSI/kg Indicted on Sidewall is the Maximum for the Tyre, Which May Not Be Proper for Your Vehicle.
- Check/Adjust Pressure when Tyres Are Cold.

#### CHECK THE FOLLOWING ITEMS MONTHLY

- TREAD AREA:  
Uneven Wear, Cuts, Bulges, Foreign Objects
- SIDEWALL:  
Ozone Cracking, Cuts, Bulges, Impact Damage

IF ANY OF THESE CONDITIONS EXIST - CONSULT A PROFESSIONAL IMMEDIATELY.



DISTRIBUTED BY

[www.sd-international.com](http://www.sd-international.com)

*These data can be changed by the manufacturer without prior notice and differently applied by regions.*

Printed on Feb. 2023

# ZETA TYRES

## 2023

### PRODUCTS MANUAL

# CHOOSE ZETA AND TAKE CONTROL

## MADE IN THAILAND

[www.zeta-tyres.com](http://www.zeta-tyres.com)





**THE BEST CHOICE**  
**A BETTER WAY FORWARD**

# WHY ZETA

---

Looking for a tyre that is not made in China?  
But one that can still be sourced at competitive prices.  
But without compromising quality and performance?

---

Introducing Zeta,  
the new premium tyre manufactured in Thailand.

---

Regardless of weather and road conditions, Zeta is the perfect choice for your driving needs.

With a variety of performance designs engineered in the USA, you will not be disappointed.

Zeta – the only tyre that fits your unique driving demands.

---

Choose Zeta and take control.

---

# PRODUCTS



**VERDANT**



**MEGLIO**



**ETALON**



**IMPERO**



**IMPERO A/T**



**CONSENSO H/T**



**IMPERO M/T**





# VERDANT



- An advanced tread design coupled with a high stylized sidewall design offers excellent driving comfort.
- Silica compound provides improved dry & wet traction along with lower rolling resistance.
- Equilibrium polyester body ply, wider steel belts plus high density jointless nylon full cover minimize tyre deformation, enhance durability and stability.



Size	LI/SI	UTQG	mm	TD	32nds	Load Capacity kg	lbs	Max.Speed Km/h	mph	Cold Infl. Press Kpa	psi
185/70R14	88H	500AA	7.8	9.8	560	1235	210	130	300	44	44
195/70R14	91H	500AA	8.0	10.1	615	1356	210	130	300	44	44
205/70R15	96H	500AA	8.0	10.1	710	1565	210	130	300	44	44
215/70R15	98H	500AA	8.3	10.5	750	1653	210	130	300	44	44
165/65R14	79H	500AA	7.8	9.8	437	963	210	130	300	44	44
175/65R14	84T XL	500AA	7.8	9.8	500	1102	190	118	340	49	49
185/65R14	86H	500AA	7.8	9.8	530	1168	210	130	300	44	44
175/65R15	88H XL	500AA	7.8	9.8	560	1235	210	130	340	49	49
185/65R15	88H	500AA	7.8	9.8	560	1235	210	130	300	44	44
195/65R15	91V	500AA	8.0	10.1	615	1356	240	149	300	44	44
205/65R15	94H	500AA	8.0	10.1	670	1477	210	130	300	44	44
205/65R16	95V	500AA	7.8	9.8	690	1521	240	149	300	44	44
215/65R16	98H	500AA	8.0	10.1	750	1653	210	130	300	44	44

Size	LI/SI	UTQG	mm	TD	32nds	Load Capacity kg	lbs	Max.Speed Km/h	mph	Cold Infl. Press Kpa	psi
185/60R14	82H	500AA	7.8	9.8	475	1047	210	130	300	44	44
195/60R14	86H	500AA	8.0	10.1	530	1168	210	130	300	44	44
165/60R15	77H	500AA	7.8	9.8	412	908	210	130	300	44	44
185/60R15	88H XL	500AA	7.8	9.8	560	1235	210	130	340	49	49
195/60R15	88V	500AA	8.0	10.1	560	1235	240	149	300	44	44
205/60R15	91V	500AA	8.0	10.1	615	1356	240	149	300	44	44
205/60R16	92V	500AA	8.0	10.1	630	1389	240	149	300	44	44
215/60R16	95V	500AA	8.3	10.5	690	1521	240	149	300	44	44
225/60R16	98H	500AA	8.3	10.5	750	1653	210	130	300	44	44
165/55R14	72H	500AA	7.8	9.8	355	783	210	130	300	44	44
185/55R15	82V	500AA	7.8	9.8	475	1047	240	149	300	44	44
195/55R15	85V	500AA	8.0	10.1	515	1135	240	149	300	44	44
205/55R16	91V	500AA	8.0	10.1	615	1356	240	149	300	44	44
215/55R16	97V XL	500AA	8.0	10.1	730	1609	240	149	340	49	49
225/55ZR16	99W XL	500AA	8.0	10.1	775	1709	270	168	340	49	49
195/50R15	82V	500AA	8.0	10.1	475	1047	240	149	300	44	44
205/50ZR16	87W	500AA	8.0	10.1	545	1201	270	168	300	44	44
205/45ZR16	87W XL	500AA	8.0	10.1	545	1201	270	168	340	49	49



# MEGLIO



- Four wide straight grooves provide efficient drainage in wet conditions for improved vehicle stability.
- A straight rib block design applied to the outside of the tyre contact patch helps to eliminate unwanted road noise and increase cornering grip and driving stability.
- The Ultra-high performance design offers drivers impressive grip in dry and wet conditions, while multiple 2D kerfs and carving edges provide improved winter traction.



Size	LI/SI	UTQG	mm	TD	32nds	Load Capacity kg	lbs	Max.Speed Km/h	mph	Cold Infl. Press Kpa	psi
225/60R18	104V XL	500AA	8.0	10.1	900	1984	240	149	340	49	
215/55ZR17	98W XL	500AA	8.0	10.1	750	1653	270	168	340	49	
225/55ZR17	101W XL	500AA	8.0	10.1	825	1819	270	168	340	49	
235/55ZR17	99W	500AA	8.3	10.5	775	1709	270	168	300	44	
225/55ZR18	102W XL	500AA	8.0	10.1	850	1874	270	168	340	49	
225/50ZR16	92W	500AA	8.0	10.1	630	1389	270	168	300	44	
205/50ZR17	93W XL	500AA	8.0	10.1	650	1433	270	168	340	49	
215/50ZR17	95W XL	500AA	8.0	10.1	690	1521	270	168	340	49	
225/50ZR17	98W XL	500AA	8.0	10.1	750	1653	270	168	340	49	
225/50ZR18	99W XL	500AA	8.0	10.1	775	1709	270	168	340	49	
235/50ZR18	101W XL	500AA	8.0	10.1	825	1819	270	168	340	49	
205/45ZR17	88 W XL	500AA	8.0	10.1	560	1235	270	168	340	49	
215/45ZR17	91W XL	500AA	8.0	10.1	615	1356	270	168	340	49	

Size	LI/SI	UTQG	mm	TD	32nds	Load Capacity kg	lbs	Max.Speed Km/h	mph	Cold Infl. Press Kpa	psi
225/45ZR17	94W XL	500AA	8.0	10.1	670	1477	270	168	340	49	
235/45ZR17	97W XL	500AA	8.0	10.1	730	1609	270	168	340	49	
245/45ZR17	99W XL	500AA	8.0	10.1	775	1709	270	168	340	49	
215/45ZR18	93W XL	500AA	8.0	10.1	650	1433	270	168	340	49	
225/45ZR18	95W XL	500AA	8.0	10.1	690	1521	270	168	340	49	
235/45ZR18	98W XL	500AA	8.0	10.1	750	1653	270	168	340	49	
245/45ZR18	100W XL	500AA	8.0	10.1	800	1764	270	168	340	49	
245/45ZR19	102W XL	500AA	8.0	10.1	850	1874	270	168	340	49	
205/40ZR17	84W XL	500AA	8.0	10.1	500	1102	270	168	340	49	
215/40ZR18	89W XL	500AA	8.0	10.1	580	1279	270	168	340	49	
225/40ZR18	92W XL	500AA	8.0	10.1	630	1389	270	168	340	49	
235/40ZR18	97W XL	500AA	8.0	10.1	730	1609	270	168	340	49	
245/40ZR18	97W XL	500AA	8.0	10.1	730	1609	270	168	340	49	
245/40ZR19	98W XL	500AA	8.0	10.1	750	1653	270	168	340	49	
265/35ZR18	97W XL	500AA	8.0	10.1	730	1609	270	168	340	49	
245/35ZR19	97W XL	500AA	8.0	10.1	730	1609	270	168	340	49	
225/35ZR20	93W XL	500AA	8.0	10.1	650	1433	270	168	340	49	
245/35ZR20	95W XL	500AA	8.0	10.1	690	1521	270	168	340	49	
255/35ZR20	97W XL	500AA	8.0	10.1	730	1609	270	168	340	49	
275/30ZR20	97W XL	500AA	8.0	10.1	730	1609	270	168	340	49	

# ETALON



- Etalon gives you the all weather handling you need for your crossover vehicle, while delivering a comfortable and quiet ride.
- Circumferential zigzag grooves resist hydroplaning by channeling water away from the tread grooves.
- Optimized tread profile design reduces rolling resistance heavily and increases fuel efficiency.
- Integrated shoulder minimizes road noise and uneven wear for quite ride.



# IMPERO



- 4 wide longitudinal grooves improves drainage performance.
- Anti-hydroplaning lateral grooves offers excellent wet performance.
- 3 center block provide straight-driving stability.
- Optimized shoulder blocks maximize grip during cornering.



Size	LI/SI	UTQG	TD		Load Capacity		Max.Speed		Cold Infl. Press	
			mm	32nds	kg	lbs	Km/h	mph	Kpa	psi
235/75R15	105H	500AA	8.3	10.5	925	2039	210	130	300	44
215/70R16	100H	500AA	8.0	10.1	800	1764	210	130	300	44
225/70R16	103H	500AA	8.0	10.1	875	1929	210	130	300	44
235/70R16	106H	500AA	8.0	10.1	950	2094	210	130	300	44
245/70R16	111T XL	500AA	8.0	10.1	1090	2403	190	118	340	49
255/70R16	111T	500AA	8.3	10.5	1090	2403	190	118	300	44
265/70R16	112T	500AA	8.3	10.5	1120	2469	190	118	300	44
245/70R17	100T	500AA	8.3	10.5	800	1764	190	118	300	44
265/70R17	115S	500AA	8.3	10.5	1215	2679	180	112	300	44
235/65R16	103H	500AA	8.0	10.1	875	1929	210	130	300	44
215/65R17	99H	500AA	8.0	10.1	775	1709	210	130	300	44
225/65R17	102H	500AA	8.0	10.1	850	1875	210	130	300	44
235/65R17	108V XL	500AA	8.0	10.1	1000	2205	240	149	340	49
245/65R17	111H XL	500AA	8.0	10.1	1090	2406	210	130	340	49
235/65R18	110H XL	500AA	8.0	10.1	1060	2337	210	130	340	49
265/65R18	114H	500AA	8.0	10.1	1180	2601	210	130	300	44
275/65R18	116H	500AA	8.0	10.1	1250	2756	210	130	300	44
225/60R17	99V	500AA	8.3	10.5	775	1709	240	149	300	44
235/60R17	103S XL	500AA	8.3	10.5	875	1929	180	112	340	49
235/60R18	107V XL	500AA	8.0	10.1	975	2149	240	149	340	49
265/60R18	110V	500AA	8.0	10.1	1060	2337	240	149	300	44
235/55R18	100V	500AA	8.0	10.1	800	1764	240	149	300	44
255/55R18	109V XL	500AA	8.0	10.1	1030	2271	240	149	340	49

Size	LI/SI	UTQG	TD		Load Capacity		Max.Speed		Cold Infl. Press	
			mm	32nds	kg	lbs	Km/h	mph	Kpa	psi
275/55ZR20	117W XL	500AA	8.3	10.5	1285	2833	270	168	340	49
245/45ZR20	103W XL	500AA	8.0	10.1	875	1929	270	168	340	49
275/45R20	110V XL	500AA	8.3	10.5	1060	2337	240	149	340	49
285/45R22	114V XL	500AA	8.3	10.5	1180	2601	240	149	340	49
305/45R22	118V XL	500AA	8.3	10.5	1320	2910	240	149	340	49
275/40ZR20	106W XL	500AA	8.3	10.5	950	2094	270	168	340	49
305/40R22	114V XL	500AA	8.3	10.5	1180	2601	240	149	340	49
265/40ZR22	106W XL	500AA	8.3	10.5	950	2094	270	168	340	49
265/35ZR22	102W XL	500AA	8.0	10.1	850	1875	270	168	340	49
295/35R24	110V XL	500AA	8.0	10.1	1060	2337	240	149	340	49
305/35ZR24	112W XL	500AA	8.3	10.5	1120	2469	270	168	340	49
315/35ZR20	110W XL	500AA	8.3	10.5	1060	2337	270	168	340	49
235/30ZR22	90W XL	500AA	8.3	10.5	600	1323	270	168	340	49
245/30ZR22	95W XL	500AA	8.0	10.1	690	1521	270	168	340	49
255/30ZR24	97W XL	500AA	8.0	10.1	730	1609	270	168	340	49

# IMPERO A/T



- Wraparound tread gives tyres a rugged look and guards against cuts, bruises and impact breaks, affords outstanding traction especially in muddy or snowy conditions.
- Reinforced wide tread gauge helps to prevent internal damage from impacts sustained when off the road.
- Thick sidewall rubber gauge helps to minimize damage from off-road impact.
- Reinforced carcass and rubber gauge improved hill climbing and steering stability both on and off the road.



Size	LI/SI	UTQG	mm	TD 32nds	Load Capacity kg	lbs	DUAL LOAD kg	lbs	Max.Speed Km/h	mph	Cold Infl. Press Kpa	psi
215/75R15	100T	600AA	9.6	12.1	800	1764	/	/	190	118	300	44
255/70R15	108S	600AA	10.4	13.1	1000	2205	/	/	180	112	300	44
265/70R15	112S	600AA	10.4	13.1	1120	2469	/	/	180	112	300	44
245/70R16	107H	600AA	10.4	13.1	975	2149	/	/	210	130	300	44
265/65R17	112T	600AA	10.4	13.1	1120	2469	/	/	190	118	300	44
31*10.50R15LT-6PR	109S	NA	12.8	16.1	1030	2271	/	/	180	112	350	50
35*12.50R20LT-12PR	126R	NA	12.2	15.4	1700	3750	/	/	170	106	550	80
33*12.50R22LT-12PR	123S	NA	12.2	15.4	1550	3415	/	/	170	106	550	80
35*12.50R22LT-12PR	126R	NA	12.2	15.4	1700	3750	/	/	170	106	550	80
LT215/85R16-10PR	115/112S	NA	11.2	14.1	1215	2680	1120	2470	180	112	550	80
LT235/85R16-10PR	120/116Q	NA	11.2	14.1	1380	3042	1260	2778	160	99	550	80
LT235/80R17-10PR	120/117S	NA	11.2	14.1	1400	3085	1285	2835	180	112	550	80
LT235/75R15-8PR	110/107S	NA	11.2	14.1	1060	2335	975	2150	180	112	450	65

Size	LI/SI	UTQG	mm	TD 32nds	Load Capacity kg	lbs	DUAL LOAD kg	lbs	Max.Speed Km/h	mph	Cold Infl. Press Kpa	psi
LT225/75R16-10PR	115/112S	NA	11.2	14.1	1215	2680	1120	2470	180	112	550	80
LT245/75R16-10PR	120/116S	NA	12.8	16.1	1380	3042	1260	2778	180	112	550	80
LT265/75R16-10PR	123/120S	NA	12.8	16.1	1550	3415	1400	3085	180	112	550	80
LT285/75R16-10PR	126/123S	NA	13.7	17.3	1700	3750	1550	3145	180	112	550	80
LT245/75R17-10PR	121/118S	NA	12.8	16.1	1450	3195	1320	2910	180	112	550	80
LT235/70R16-6PR	104/101S	NA	10.9	13.7	900	1984	825	1819	180	112	350	50
LT265/70R16-10PR	121/118S	NA	12.5	15.7	1450	3195	1320	2910	180	112	550	80
LT245/70R17-10PR	119/116S	NA	12.8	16.1	1360	3000	1250	2755	180	112	550	80
LT265/70R17-10PR	121/118S	NA	12.8	16.1	1450	3195	1320	2910	180	112	550	80
LT285/70R17-10PR	121/118Q	NA	13.7	17.3	1450	3195	1320	2910	160	99	450	65
LT265/70R18-10PR	124/121S	NA	12.8	16.1	1600	3525	1450	3195	180	112	550	80
LT275/70R18-10PR	125/122S	NA	12.8	16.1	1650	3460	1500	3305	180	112	550	80
LT275/65R18-10PR	123/120S	NA	12.8	16.1	1550	3415	1400	3085	180	112	550	80
LT285/65R18-10PR	125/122R	NA	12.2	15.4	1650	3640	1500	3305	170	106	550	80
LT325/65R18-10PR	127/124S	NA	12.2	15.4	1750	3860	1600	3525	180	112	450	65
LT275/65R20-10PR	126/123S	NA	12.8	16.1	1700	3750	1550	3415	180	112	550	80
LT265/60R20-10PR	121/118S	NA	12.8	16.1	1450	3195	1320	2910	180	112	550	80
LT285/60R20-10PR	125/122S	NA	13.7	17.3	1650	3640	1500	3305	180	112	550	80
LT325/60R20-10PR	126/123S	NA	12.2	15.4	1700	3750	1550	3415	180	112	450	65
LT265/50R20-10PR	121/118S	NA	12.2	15.4	1450	3195	1320	2910	180	112	550	80
LT275/55R20-10PR	120/117S	NA	12.2	15.4	1400	3085	1285	2833	180	112	550	80
LT285/55R20-10PR	122/119S	NA	12.2	15.4	1500	3305	1360	3000	180	112	551	80
LT305/55R20-10PR	121/118S	NA	12.2	15.4	1450	3195	1320	2910	180	112	450	65

## CONSENSO H/T



- 3D wave-patterned kerfs design used in tyres provide improved grip and handling performance by minimizing block movement when driving, heavily improved all season performance.
- Multi-depth lateral lugs provide improved performance in wet and snow conditions.
- 4 straight grooves channel provides sure-footed performance in both wet and dry conditions.
- High stiffness center block improves steering performance.
- Button elements sized for good snow and wet traction, yet interlocking geometry maintains rib stiffness for handling.



## IMPERO M/T



- Specially designed tread block provide better grip in mud, sand and snow.
- Unique stone-Ejector grooves along with a rugged shoulder help to prevent damage from impact.
- Optimized void-to-rubber ratio provides excellent traction.
- Large surface area tread blocks provide increased grip.



Size	LI/SI	UTQG	mm	TD	32nds	Load Capacity	kg	lbs	DUAL LOAD	kg	lbs	Max.Speed	Km/h	mph	Cold Infl. Press	Kpa	psi
LT215/85R16-10PR	115/112S	NA	9.9	12.5	1215	2680	1120	2470	180	112	550	80					
LT235/85R16-10PR	120/116Q	NA	9.9	12.5	1380	3042	1260	2778	160	99	550	80					
LT235/80R17-10PR	120/117Q	NA	9.9	12.5	1400	3085	1285	2835	160	99	550	80					
LT225/75R16-10PR	115/112S	NA	9.9	12.5	1215	2680	1120	2470	180	112	550	80					
LT245/75R16-10PR	120/116S	NA	10.7	13.5	1380	3042	1260	2778	180	112	550	80					
LT265/75R16-10PR	123/120Q	NA	10.7	13.5	1550	3415	1400	3085	160	99	550	80					
LT245/75R17-10PR	121/118Q	NA	10.7	13.5	1450	3195	1320	2910	160	99	550	80					
LT245/70R17-10PR	119/116S	NA	10.7	13.5	1360	3000	1250	2755	180	112	550	80					
LT265/70R17-10PR	121/118Q	NA	10.7	13.5	1450	3195	1320	2910	160	99	550	80					
235/75R15	109H	500AA	8.2	10.3	1030	2271	/	/	210	130	340	49					
215/70R16	100H	500AA	8.2	10.3	800	1764	/	/	210	130	300	44					
225/70R16	103T	500AA	8.2	10.3	875	1929	/	/	190	118	300	44					
235/70R16	106H	500AA	8.2	10.3	950	2094	/	/	210	130	300	44					
245/70R16	107H	500AA	8.2	10.3	975	2149	/	/	210	130	300	44					
255/70R16	111H	500AA	8.2	10.3	1090	2403	/	/	210	130	300	44					
265/70R16	112H	500AA	8.2	10.3	1120	2469	/	/	210	130	300	44					
275/60R20	114T	500AA	11.5	14.5	1180	2601	/	/	190	118	240	35					
275/55R20	117H	500AA	11.5	14.5	1285	2833	/	/	210	130	340	49					

Size	LI/SI	UTQG	mm	TD	32nds	Load Capacity	kg	lbs	Max.Speed	Km/h	mph	Cold Infl. Press	Kpa	psi
33X12.50R15LT-6pr	108Q	NA	15.7	19.8	1000	2205	160	99	250	35				
33x12.50R18LT-10pr	118Q	NA	15.7	19.8	1320	2910	160	99	450	65				
33x12.50R20LT-10pr	114Q	NA	15.4	19.4	1180	2600	160	99	450	65				
35X12.50R15LT-6pr	113Q	NA	15.7	19.8	1150	2535	160	99	250	35				
35X12.50R17LT-10pr	121Q	NA	15.7	19.8	1450	3195	160	99	450	65				
35X12.50R18LT-10pr	123Q	NA	15.7	19.8	1550	3415	160	99	450	65				
35X12.50R20LT-10pr	121Q	NA	15.7	19.8	1450	3195	160	99	450	65				
LT285/65R18-10pr	125/122Q	NA	15.7	19.8	1650	3460	160	99	550	80				