



Driving Your Harvest!



**OFF THE
ROAD TYRES**



OTR TYRE



OTR TYRE »

H108A L-3/E-3 GENERAL BLOCK (S TREAD)

Specially desinged for cut and heat resistant compound.
Regular type of tread pattern suitable for hard rock surface and haulage service.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)		Type	Code
						50km/h	10km/h	50km/h	10km/h		
14. 00-24	16	25	10. 0	375	1370	4000	7300	375	550	TT/TL	H108A L-3 E-3
	20					4625	8500	475	700		
	24					5150	9500	575	850		
	28					5600	10000	650	925		
16. 00-24	20	28	11. 25/2. 0	430	1495	5450	9750	400	550		
	24					6000	10600	475	650		
	28					6700	11500	575	750		
	32					7300	12500	650	875		
17. 5-25	16	28	14. 00/1. 5	445	1350	4250	7300	300	475		
	20					5000	8250	400	575		
20. 5-25	20	30	17. 00/2. 0	520	1490	6000	9500	325	450		
	24					6700	10300	400	525		
	28					7500	11500	475	625		
23. 5-25	20	33	19. 50/2. 5	595	1615	7300	10900	300	375		
	24					8000	12500	350	475		
	28					8750	13600	400	550		
26. 5-25	28	35	22. 00/3. 0	675	1750	10000	15500	350	475	TL	
	32					11200	17000	425	550		
29. 5-25	28	38	25. 00/3. 5	750	1875	11500	17500	325	425		
	34					12500	19000	375	500		
Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)		Type	Code
16/70-24	14	24. 5	13 (SDC)	410	1175	5600		450		TT	H108A L-3 E-3
16/70-20	14	24	13 (SDC)	410	1075	5150		450			
	18					5800		550			
14/90-16	10	16	7. 0N	270	882	1530		350			
12. 00-16	12	17	6. 5H	255	890	1600		420			
8. 25-16	8	16	6. 5	235	865	1530		300			
7. 50-16	8	16	5. 5	215	815	750		150			

OTR TYRE »

H108B L-3/E-3 LARGE BLOCK (S TREAD)

Optimized pattern design for mining and quarrying operations.
Excellent abrasion.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)		Type	Code
						50km/h	10km/h	50km/h	10km/h		
17.5-25	16	28	14.00/1.5	445	1350	4250	7300	300	475	TT/TL	H108B L-3 E-3
	20					5000	8250	400	575		
23.5-25	20	33	19.50/2.5	595	1615	7300	10900	300	375		
	24					8000	12500	350	475		
	28					8750	13600	400	550		

H108C NEW L-3/E-3 LOADER MASTER(Z TREAD)

New Z tread tyre for low intensity application of Loader/Earthmover/Grader.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)		Type	Code
						50km/h	10km/h	50km/h	10km/h		
16/70-16	10	19	10. 00G	335	910	—	1600	—	280	TT	H108C L-3 E-3 G-3
20. 5/70-16	10	19	10. 00G	335	910	—	1600	—	280		
15. 5-25	12	24. 5	12. 00/1. 3	395	1275	3250	5600	250	400	TT/TL	
	16					3850	6750	325	525		
17. 5-25	16	28	14. 00/1. 5	445	1350	4250	7300	300	475		
	20					5000	8250	400	575		
20. 5-25	20	30	17. 00/2. 0	520	1490	6000	9500	325	450		
	24					6700	10300	400	525		
23. 5-25	20	33	19. 50/2. 5	595	1615	7300	10900	300	375		
	24					8000	12500	350	475		
16. 00-25	28	30	11. 25/2. 0	430	1495	6700	11500	575	750		
	32					7300	12500	650	875		

OTR TYRE »

H109 IND-3S SUPER EXTRA SLICK

Suitable for loader and dozer.
Special compound and smooth pattern design is suitable for heat and cut resistant.
Smooth tread with a reinforced sidewall protector for hard working area and underground mining.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)	Pressure (kpa)	Type	Code
23.5-25	20	40	19.50/2.5	595	1615	10900	375	TT/TL	H109 L-3 E-3 G-3
	24		19.50/2.5	595	1615	12500	475		
17.5-25	20	28	14.00/1.5	445	1350	8250	575		
	24		14.00/1.5	445	1350	9000	600		

H166 IND-3/E-3 OUTSTANDING QUALITY MINING & PORT EXTRA

Suitable for use in port and mining for long mileage.
Specially designed pattern with extra strong tread and reinforced sidewall protector.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)		Pressure (kpa)		Type	Code
						50km/h	10km/h	50km/h	10km/h		
16.00-25	28	32	11.25/2.0	430	1550	11500	6700	750	575	TT/TL	H166 IND-3 E-3
	32					12500	7300	875	650		
	36					13600	7750	975	725		
	40					14500	8200	1075	800		
18.00-25	32	36	13.00/2.5	500	1675	15000	8750	750	575		
	36					16000	9250	850	625		
	40					17000	9750	950	700		
	44					18000	10500	10300	775		
18.00 33	32	36	13.00/2.5	500	1820	17500	10000	750	575		
	36					18500	10600	850	625		
	40					20000	11100	950	675		
21.00-25	40	43	15.00/3.0	570	1750	20600	11800	825	625		

OTR TYRE >>

H167 L-5 EXTRA HIGH TREAD (ROCK SERVICE)

Suitable for wheel loader with extra deep tread and cut resistant compound for rocky surface and mining service.
Excellent traction and stability comfortable / Long life tread design.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)	Pressure (kpa)	Type	Code
17.5-25	24	63.5	13.00/1.5	445	1400	8950	650	TT/TL	H167 L-5
23.5-25	24	78	19.5/2.5	595	1675	12500	475		
	28		19.5/2.5	595	1675	13600	550		
	32		19.5/2.5	595	1675	14000	600		

H168 G-2/L-2 SUPER GRADER LOADER SPECIAL

Suitable for wheel loader with extra deep tread and cut resistant compound for rocky surface and mining service.
Excellent traction and stability comfortable / Long life tread design.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg) @ 40km/h	Pressure (kpa) @ 40km/h	Type	Code
13.00-24	12	24	8.00TG	335	1280	2725	300	TT/TL	H168 G-2 L-2
	16					3200	400		
14.00-24	12	25	8.00TG	360	1350	3450	325		
	16					3650	375		
17.5-25	16	26	14.00/1.5	445	1350	3350	275		
	20					3650	325		

OTR TYRE >>

H169 E-7 HEATMASTER SAND/DESERT TIRE

The combination of wide tread, round shoulder and streamlined pattern design provides stable ride, good floating force, excellent steering ability on sand ground road surface.
With HEATMASTER compound for desert application.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)	Pressure (kpa)	Type	Code
9.00-16	8	10	6.50H	860	245	1320	310	TT	H169 E-7
9.00-17	8	10	7J	880	245	1320	310		
14.00-20	18	10	10.00W	1207	355	4125	245		
16.00-20	18	14	10.00W	1323	419	5450	245		

H176 E-2 HEAVY COUNTRY CROSS TIRE (SUPER MILITARY APP.)

Super country-cross pattern is suitable for heavy trucks and other machines.
Military tech design can support using in terrible conditions such as desert, grass, forest, mountain road etc.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg)	Pressure (kpa)	Max Speed (km/h)	Type	Code
1500x600-635	14	30	500x635	600	1500	5750	380	60	TT	H176 E-2
1500x600-635	22		500x635	600	1500	7050	550	60		
1600x600-685	24	32	500x685	600	1600	7900	440	60		

OTR TYRE >>

H178 R-3/C-2/E-7 MULTI-PURPOSE FLOATATION TYRE

Wide Section for good flotation force and steering ability.
Special for desert transportation and road compactor application.



Size	PR	S.R.	S.W. (mm)	O.D. (mm)	Pressure (kpa) @ 10km/h	Loading (kg) @ 10km/h	Type	Code
23. 1-26	12	DW20	595	1500	200	5150	TT/TL	H178
	14				230	5600		R 3
	16				260	6150		C 2 E-7



FORKLIFT TYRE



FORKLIFT TYRE >>

H989 INDUSTRIAL MASTER (NHS)

Developed for heavy use on forklifts and other industrial vehicles. With its wide and extra deep tread provides stronger traction, longer life and puncture resistance.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Max Loading (kg)	Pressure (kpa)	Type	Code
5.00-8	8	11	3.50D	470	137	1000	790	TT	H989 NHS
16X6-8	10	11	4.33R	425	152	1085	860		
18X7-8	16	11	4.33R	465	173	1695	1000		
6.00-9	8	11	4.00F	540	160	1505	860		
7.00-9	8	13	5.00S	590	190	1995	860		
21X8-9	14	15	6.00E	535	200	2040	1000		
6.50-10	8	12	5.00F	590	175	1655	790		
23X9-10	16	16	6.50F	595	225	2810	1030		
7.00-12	12	13	5.00S	676	190	2375	860		
8.25-12	12	18	6.5	765	235	3060	720		
27X10-12	16	16	8.00G	690	255	3585	1000		
300-15	20	21	8.0	848	300	5940	930		
7.50-15	16	19	6.0	780	215	3550	1000		
7.00-15	14	19	5.5	750	200	3140	1000		
8.25-15	12	18	6.5	840	235	3545	720		
28X9-15	12	19	7.0	710	220	3050	970		
9.00-20	16	20	7.0	1025	259	5595	860		
10.00-20	18	22	7.5	1078	278	6475	890		
12.00-20	20	25	8.5	1135	315	7400	900		

FORKLIFT TYRE >>

H990 XTRA WALL AND MASSIVE TREAD BLOCK

New pattern design supports longer working life. Special compound could be used in much more hard working sites. Non-symmetric tread offers more traction power and better wear-ability.



Size	PR	T.D. (mm)	S.R.	O.D. (mm)	S.W. (mm)	Loading (kg)	Pressure (kpa)	Type	Code
8.25-15	16	22	6.50	840	242	4470	880	TT	H990 NHS
28X9-15	14	22	7.00	713	220	3145	780		
	16					3400	880		
7.00-12	14	20	5.00	676	192	3085	980		
6.50-10	12	21	5.00	590	185	2095	880		
7.00-9	10	19	5.00	590	192	1995	860		
6.00-9	10	18	4.00	540	168	1730	835		
5.00-8	10	16	3.50	470	138	1305	880		
18X7-8	14	18	4.33R	465	173	1505	970		
	16					1695	1000		

FORKLIFT TYRE >>

TW898 EXTRA POWER STRONG INDUSTRIAL

Pattern design with wide contact area increases traction.
Reinforced tie bar between the zig-zag pattern.
New compound for outstanding durability / longer life.



Size	PR	T.D. (mm)	S.R.	O.D. (mm)	S.W. (mm)	Loading (kg)	Pressure (kpa)	Type	Code
8.25-15	16	25	6.50	845	242	4470	880	TT	TW898 IND
7.50-16	16	22	6.00GS	810	212	3870	880		

DT1000 SUPER DEEP TREAD & WIDE CROWN SERIES

Developed for heavy use on forklifts and other industrial vehicles.
With its wide and extra deep tread provides stronger traction, longer life
and puncture resistance.



Size	PR	T.D. (mm)	S.R.	O.D. (mm)	S.W. (mm)	Loading (kg)	Pressure (kpa)	Type	Code
8.25-15	16	33.5	6.50	851	246	4470	880	TT	DT1000 NHS
7.00-12	14	33.5	5.00	630	200	3085	980		
6.50-10	12	31	5.00	599	185	2095	880		



SPECIALITY IND TYRE



SPECIALITY IND TYRE >>

AS2000 L-2 URBAN INDUSTRIAL

Developed for urban excavator and industrial trailer vehicles, by new compound for outstanding durability. Extra deep tread provides longer life and puncture resistance. Reinforced tie bar between the zig-zag block pattern.



Size	PR	T.D. (mm)	S.R.	O.D. (mm)	S.W. (mm)	Loading (kg)	Pressure (kpa)	Type	Code
9.00-20	16	28	7.00	1025	260	4060	740	TT	AS 2000 L-2 NHS

H966 G-2/L-2/E-2 EXCAVATOR TYRE(X'C)

Optimized pattern design for excavator. Excellent abrasion and traction and self-cleaning.



H966A H966B

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 10km/h	Pressure (kpa) @ 10km/h	Type	Code
8.25-20	14	20	6.5	235	992	3865	830	TT	H966A G-2/L-2/E-2
9.00-20	16	22	7.0	259	1038	4725	860		
10.00-20	18	22	7.5	278	1073	5470	890		
11.00-20	16	24	8.0	293	1105	5405	760		H966A G-2/L-2/E-2
	18					6000	825		
9.00-20	16	25	7.0	259	1040	4725	860		H966B G-2

SPECIALITY IND TYRE >>



SKS-1(R-4)



SKS-3(L-5)



SKS-4(L-2)



SKS-PLUS

SKS-1/3/4 SKID STEER TYRE

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg)	Pressure (kpa)	Type	Code
27X8.5-15	8	13	7JA	678	215	1030	350	TL	SKS-1 R-4
10-16.5	8	19	8.25	773	264	1880	410		
10-16.5	10	19	8.25	773	264	2135	520		
12-16.5	12	19	9.75	831	307	2865	550		
12-16.5	14	19	9.75	831	307	3075	620		
14-17.5	14	19	10.5	921	349	3875	550		
15-19.5	14	21	11.75	1019	389	4565	485		SKS-3 L-5
10-16.5	12	35	8.25	785	270	2865	550		
12-16.5	14	42	9.75	845	314	3075	620		
12-16.5	14	25	9.75	842	325	3075	620		
10-16.5	12	27	8.25	785	270	2375	620		
12-16.5	14	35	9.75	840	315	3075	620		

SKS-1 R-4 STANDARD

Optimized pattern design for loader/grader with excellent traction and self-cleaning in a muddy ground.

SKS-3 L-5 EXTRA DEEP

Application to Skid Steer loader and scraper tyre for hard working area. Good wear resistance, with extra deep tread and side-skidding resistance.

SKS-4 L-2 EXTR FLOATING

For loaders and dozers operations on rock, coal and earth. Separate lugs and tapered for greater traction and self-cleaning.

Extra wide tread profile for better land ratio and High floating force.

SKS-PLUS A/T SKID STEER TIRE

For loaders and dozers operations on rock, coal and earth.

Extra wide tread profile for better land ratio and High floating force.

SPECIALITY IND TYRE >>

H658 R-4 INDUSTRIAL TYRE

Very good traction and better tire life.
Good resistance to tearing and cracking.
Resistance to cuts, abrasions and high load capacity.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30 km/h	Pressure (kpa) @ 30 km/h	Type	Code
16. 9-24	10	27	W15L	430	1323	2230	200	TL	H658 R-4
	12					2440	240		
16. 9-28	10	27	W15L	430	1423	2380	200		
	12					2605	240		
18. 4-26	10	27	W16L	467	1438	2645	180		
	12					2985	230		
17. 5L-24	10	26	W15L	445	1253	1725	190		
	12					1925	250		
19. 5L-24	10	27	DW16	495	1328	1925	170		
	12					2145	210		
21L-24	10	29	DW18	533	1388	2090	150		
	12					2410	190		
	16					2795	250		



H659 R-4 TRACTION IMPLEMENT/BACKHOE

Excellent traction and flushing / Good resistance to cracking.
Strengthen and stabilize tread under severe operating condition.

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30 km/h	Pressure (kpa) @ 30 km/h	Type	Code
10. 5/80-18	10	22	9	274	1323	1935	370	TL	H659 R-4
	12					2150	430		
12. 5/80-18	10	26	9	308	987	2375	310		
	12					2625	370		
	14					2910	430		
	16					3130	490		

SPECIALITY IND TYRE >>

H661 F-3 INDUSTRIAL FRONT

Husky industrial rib design, wide profile for front backhoe loader service.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30 km/h	Pressure (kpa) @ 30 km/h	Type	Code
11L-15	10	12	8LB	280	810	1190	340	TL	H661 F-3
	12					1355	420		
11L-16	10	12	8LB	280	835	1240	340		
	12					1395	420		



H663 I-1 FARM SPECIALIST IMPLEMENT

Multi rib farm tire designed for flotation for use on farm implement, wagons, tanks, carts and other pull behind vehicles.

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30 km/h	Pressure (kpa) @ 30 km/h	Type	Code
9. 5L-15	8	8	8LB	240	765	1100	280	TL	H663 I-1
	10					1310	340		
11L-15	8	9	W8L	280	775	1130	220		
	10					1285	280		
	12					1345	340		
12. 5L-15	8	9	W10L	317	823	1350	220		
	12					1730	330		
	14					1830	360		
11L-16	8	9	W8L	280	800	1175	220		
	10					1340	280		
	12					1515	340		



PNEUMATIC SOLID TYRE



PNEUMATIC SOLID TYRE »

H991A XTRA WALL AND MASSIVE TREAD BLOCK SOLID

High quality raw material support and unique formula design.



Size	T.D.	S.R.	O.D.	S.W.	Max Loading (kg)				Code	
	(mm)		(mm)	(mm)	Forklift		Other Industrial			
					10km/h		16km/h			10km/h
					Load	Rota	Load	Rota		
300-15 (315/70-15)	29	8.0	838	300	6895	5305	6300	4845	5310	H991A SOLID

H991B EXCELLENT VIBRATION CONTROL PATTERN SOLID

Aggressive pattern for port trailer and forklift.
High load & excellent wear-resistance.



Size	T.D.	S.R.	O.D.	S.W.	Max Loading (kg)					Code
	(mm)		(mm)	(mm)	Forklift				Other Industrial	
					10km/h		16km/h		10km/h	
					Load	Rota	Load	Rota		
9.00-20	40	6.5	1038	259	6160	5135	5630	4690	4745	H991B SOLID
9.00-20		7.0	1038	259	6365	5305	5815	4845	4905	
10.00-20	40	7.5	1073	278	7075	5895	6460	5385	5450	
10.00-20		8.0	1073	278	7300	6085	6670	5560	5630	
11.00-20	45	7.5	1095	300	7470	6225	6820	5685	5750	
11.00-20		8.0	1095	300	7715	6430	7045	5870	5940	
12.00-20	45	8.0	1180	310	8640	7200	7885	6570	6650	
12.00-20		8.5	1180	310	8920	7435	8140	6785	6865	

PNEUMATIC SOLID TYRE »

H992A SUPER STRONG LARGE BLOCK SOLID

Litter rolling resistance & low heat generating.
Little energy conservation & strong rockfall resistance.
It's the best choice for balanced forklift and other industrial vehicles.



Size	T.D.	S.R.	O.D.	S.W.	Max Loading (kg)					Code
	(mm)		(mm)	(mm)	Forklift				Other Industrial	
					10km/h		16km/h		10km/h	
					Load	Rota	Load	Rota		
400-8	20	3.0	423	121	1090	840	995	765	840	H992A SOLID
		3.75	423	125	1175	905	1080	830	910	
5.00-8	24	3.0	469	146	1255	965	1145	880	960	
18*7-8	24	4.33	457	170	2430	1870	2215	1705	1870	
6.00-9	24	4.0	545	160	1975	1520	1805	1390	1520	
6.50-10	28	5.0	597	178	2715	2090	2485	1910	2095	
7.00-9	28	5.0	578	185	2670	2005	2440	1875	2055	
7.00-12	29	5.0	683	192	3105	2390	2835	2180	2390	
8.25-12	38	6.5	735	236	3425	2635	3125	2405	2635	
8.15-15+B2 (28X9-15) (225/75-15)	35	7.0	706	225	4060	3125	3710	2855	3125	
8.25-15	38	6.5	847	236	5085	3910	4640	3570	3910	
300-15 (315/70-15)	29	8.0	838	300	6895	5305	6300	4845	5310	

PNEUMATIC SOLID TYRE »

H992B EXTRA POWER STRONG INDUSTRIAL SOLID

High quality raw material support and unique formula design.
The tyre enjoys outstanding performance at all aspects.



Size	T.D.	S.R.	O.D.	S.W.	Max Loading (kg)					Code
	(mm)		(mm)	(mm)	Forklift				Other Industrial	
					10km/h		16km/h		10km/h	
					Load	Rota	Load	Rota		
5.00-8	24	3.0	469	146	1255	965	1145	880	960	H992B SOLID
18*7-8	24	4.33	457	170	2430	1870	2215	1705	1870	
6.00-9	24	4.0	545	160	1975	1520	1805	1390	1520	
6.50-10	28	5.0	597	178	2715	2090	2485	1910	2095	
7.00-9	28	5.0	578	185	2670	2005	2440	1875	2055	
7.00-12	29	5.0	683	192	3105	2390	2835	2180	2390	
8.25-12	38	6.5	735	236	3425	2635	3125	2405	2635	
8.15-15 (28X9-15) (225/75-15)	35	7.0	706	225	4060	3125	3710	2855	3125	
8.25-15	38	6.5	847	236	5085	3910	4640	3570	3910	

H993 PERFECT BALANCE INNOVATIVE TREAD SOLID

High land ratio for longer life.
It's the best choice for balanced forklift and other industrial vehicles.



Size	T.D.	S.R.	O.D.	S.W.	Max Loading (kg)					Code
	(mm)		(mm)	(mm)	Forklift				Other Industrial	
					10km/h		16km/h		10km/h	
					Load	Rota	Load	Rota		
16X6-8	17	4.33	418	162	1545	1190	1410	1085	1185	H993 SOLID
21X8-9	27	6.0	535	207	2890	2225	2645	2035	2230	
23X9-10	26	6.5	595	225	3730	2870	3405	2620	2865	



AGRICULTURE TYRE



H657-1



H657-2



H657-3



H657-4



H657-5



H657-6



H657-7



H657-8



H657-10



H657-11



H657-12



H657-13



H657-14



H657-15

H657

R-1 SUPER FARM TYRE

For general farm tractors.
Provides good cutting resistance and longer lifetime.

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @30km/h	Pressure (kpa) @30km/h	Type	Code
6.00-12	6	20	4.50E	165	640	405	250	TT	H657-1 R-1
6.00-12	6	20	4.50E	165	640	405	250	TT	H657-2 R-1
6.00-12	6	23	4.50E	165	640	405	250	TT	H657-3 R-1
6.00-16	6	24	4.50E	165	745	495	250	TT	H657-4 R-1
7.50-16	8	22	5.50F	205	810	800	280	TT	H657-5 R-1
11.2-24	10	32	W10	285	1105	1380	300	TT	H657-6 R-1
16.9-34	12	39	W15L	430	1585	2945	240	TT	H657-6 R-1
18.4-34	12	36	W16L	467	1655	3375	230	TT	H657-6 R-1
11.2-28	10	35	W10	285	1205	1515	300	TT	H657-7 R-1
7.5-20	8	25.5	5.50F	205	910	900	250	TT	H657-7 R-1
8.3-24	8	30	W7	210	995	950	300	TT	H657-7 R-1
9.5-20	10	28	W8	240	950	1190	370	TT	H657-7 R-1
9.5-24	10	31	W8	240	1050	1300	370	TT	H657-7 R-1
8.3-20	8	28	W7	210	895	880	300	TT	H657-8 R-1
15.5/80-24 (400/80-24)	12	35	13.0	384	1262	2900	300	TT	H657-9 R-1
15.5/80-24 (400/80-24)	16	35	13.0	384	1262	3350	400	TT	H657-9 R-1
9.5-20	10	27	W8	240	950	1190	370	TT	H657-10 R-1
14.9-26	12	42	W13	378	1315	2310	260	TT	H657-11 R-1
15.5-38	12	34	W14L	395	1570	2700	260	TT	H657-12 R-1
18.4-30	12	35	W16L	467	1550	3180	230	TT	H657-12 R-1
12.4-24	10	36	W11	315	1160	1650	280	TT	H657-13 R-1/LS-1
12.4-28	10	36	W11	315	1260	1760	280	TT	H657-13 R-1/LS-1
14.9-24	10	38	W13	378	1265	1990	230	TT	H657-14 R-1/LS-1
14.9-28	12	38	W13	378	1365	2120	230	TT	H657-14 R-1/LS-1
18.4-38	12	41	W16L	467	1755	3575	230	TT	H657-14 R-1/LS-1
15.00-24	12	37	DW14	410	1330	2800	280	TT	H657-15 R-1/LS-1



H889



H206



H207



H208

H889 H206 H207 H208

AG FRONT WHEEL & TRAILER WHEEL

Long tyre life with wear resistance.

Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30km/h	Pressure (kpa) @ 30km/h	Type	Code
5.00-14	4	7	3.00D	130	620	365	340	TT	H889
4.50-14	4	7	3.00D	122	606	345	340		
5.00-14	8	9.5	3.00D	130	620	500	420		
4.50-14	8	8	3.00D	122	606	400	420	TT	H206
6.00-16	6	8	4.00E	160	740	560	340	TT	H207
5.50-16	6	8	4.00E	150	710	525	370		
5.00-16	6	7.5	4.00E	142	680	500	370		
4.50-16	6	7	3.00D	130	655	400	390		
4.00-14	4	7	3.00D	110	590	270	340		
4.00-12	4	7	3.00D	110	535	250	340		

H209

F-2 TRIPLE RIB FARM STEERING

Better Steering with good stability / Self cleaning and damage resistance.
Better tire life / High load capacity.



Size	PR	T.D. (mm)	S.R.	S.W. (mm)	O.D. (mm)	Loading (kg) @ 30km/h	Pressure (kpa) @ 30km/h	Type	Code
11.00-16	10	23	W10L	315	970	1485	310	TT/TL	H209
10.00-16	10	23	W8L	275	910	1325	340		
7.50-16	8	14	5.50F	205	810	870	370		
5.50-16	6	13	4.00E	150	710	525	370	TT	F-2
5.00-15	6	9.5	4J	140	665	465	420		
4.00-16	4	8	3.00D	110	640	300	340		
4.00-14	4	7	3.00D	110	590	270	340		

RIGHT TYRE BETTER RESULTS!

