

**HOW TO SELECT A TIRE**

- Consult Vehicle Owner's Manual or Door Placard for Proper Tire Size and Load/Speed Index
- Consider Average Vehicle Usage (Extended Highway Use, Off-Road, etc.)

**MOUNTING/DISMOUNTING/SERVICE:**

- Only Allow Trained Professionals to Mount, Dismount, or Service Your Tires.

**TIRE PRESSURE**

- Consult Vehicle Owner's Manual or Door Placard for Proper Pressure for Your Vehicle. PSI/kg Indicated on Sidewall is the Maximum for the Tire, Which May Not Be Proper for Your Vehicle.
- Check/Adjust Pressure when Tires Are Cold.

**CHECK THE FOLLOWING ITEMS MONTHLY**

- TREAD AREA:  
Uneven Wear, Cuts, Bulges, Foreign Objects
- SIDEWALL:  
Ozone Cracking, Cuts, Bulges, Impact Damage

*IF ANY OF THESE CONDITIONS EXIST - CONSULT A PROFESSIONAL IMMEDIATELY.*

Printed on Oct. 2025



**DISTRIBUTED BY**

[www.sd-international.com](http://www.sd-international.com)

*These data can be changed by the manufacturer without prior notice and differently applied by regions.*



[www.zetatireusa.com](http://www.zetatireusa.com)





# WHY ZETA

Looking for a tire that is not made in China?  
But one that can still be sourced at competitive prices.  
and without compromising quality and performance?

---

**“** Introducing ZETA,  
the new premium tire manufactured in Thailand.

Regardless of weather and road conditions, Zeta  
is the perfect choice for your driving needs.  
With a variety of performance designs engineered  
in the USA, you will not be disappointed.  
Zeta – the only tire that fits your unique driving  
demands.

---

**Choose ZETA and take control.**

# 2026 ZETA TIRES LINE UP



05 **VERDANT**  
HP

09 **ETALON**  
CUV

13 **ARTORIA EV**  
EV

19 **IMPERO A/T**  
AT

21 **PANTHER CLAW R/T**  
RT

07 **MEGLIO**  
UHP

11 **IMPERO**  
SUV

15 **CONSENSO H/T**  
HT

25 **IMPERO M/T**  
MT

29 **CITY TRANS**  
VAN



## VERDANT HP



- An advanced tread design coupled with a high stylized sidewall design offers excellent driving comfort.
- Silica compound provides improved dry & wet traction along with lower rolling resistance.
- Equilibrium polyester body ply, wider steel belts plus high density jointless nylon full cover minimize tire deformation, enhance durability and stability.



Size	LI/SI	UTQG	TD		Load Capacity		Max.Speed	
			mm	32nds	kg	lbs	Km/h	mph
185/70R14	88H	500AA	7.8	9.8	560	1235	210	130
195/70R14	91H	500AA	8.0	10.1	615	1356	210	130
205/70R15	96H	500AA	8.0	10.1	710	1565	210	130
215/70R15	98H	500AA	8.3	10.5	750	1653	210	130
165/65R14	79H	500AA	7.8	9.8	437	963	210	130
175/65R14	84T XL	500AA	7.8	9.8	500	1102	190	118
185/65R14	86H	500AA	7.8	9.8	530	1168	210	130
175/65R15	88H XL	500AA	7.8	9.8	560	1235	210	130
185/65R15	88H	500AA	7.8	9.8	560	1235	210	130
195/65R15	91V	500AA	8.0	10.1	615	1356	240	149
205/65R15	94H	500AA	8.0	10.1	670	1477	210	130
205/65R16	95V	500AA	7.8	9.8	690	1521	240	149
215/65R16	98H	500AA	8.0	10.1	750	1653	210	130
185/60R14	82H	500AA	7.8	9.8	475	1047	210	130
195/60R14	86H	500AA	8.0	10.1	530	1168	210	130
165/60R15	77H	500AA	7.8	9.8	412	908	210	130
185/60R15	88H XL	500AA	7.8	9.8	560	1235	210	130
195/60R15	88V	500AA	8.0	10.1	560	1235	240	149
205/60R15	91V	500AA	8.0	10.1	615	1356	240	149
205/60R16	92V	500AA	8.0	10.1	630	1389	240	149
215/60R16	95V	500AA	8.3	10.5	690	1521	240	149
225/60R16	98H	500AA	8.3	10.5	750	1653	210	130
165/55R14	72H	500AA	7.8	9.8	355	783	210	130
185/55R15	82V	500AA	7.8	9.8	475	1047	240	149
195/55R15	85V	500AA	8.0	10.1	515	1135	240	149
195/55ZR16	91W XL	500AA	8.0	10.1	615	1356	270	168
205/55R16	91V	500AA	8.0	10.1	615	1356	240	149
215/55R16	97V XL	500AA	8.0	10.1	730	1609	240	149
225/55ZR16	99W XL	500AA	8.0	10.1	775	1709	270	168
195/50R15	82V	500AA	8.0	10.1	475	1047	240	149
205/50ZR16	87W	500AA	8.0	10.1	545	1201	270	168
205/45ZR16	87W XL	500AA	8.0	10.1	545	1201	270	168



## MEGLIO

UHP



- Four wide straight grooves provide efficient drainage in wet conditions for improved vehicle stability.
- A straight rib block design applied to the outside of the tire contact patch helps to eliminate unwanted road noise and increase cornering grip and driving stability.
- The Ultra-high performance design offers drivers impressive grip in dry and wet conditions, while multiple 2D kerfs and carving edges provide improved winter traction.



Size	LI/SI	UTQG	TD mm	TD 32nds	Load Capacity kg	Load Capacity lbs	Max.Speed Km/h	Max.Speed mph
225/60R18	104V XL	500AA	8.0	10.1	900	1984	240	149
215/55ZR17	98W XL	500AA	8.0	10.1	750	1653	270	168
225/55ZR17	101W XL	500AA	8.0	10.1	825	1819	270	168
235/55ZR17	99W	500AA	8.3	10.5	775	1709	270	168
225/55ZR18	102W XL	500AA	8.0	10.1	850	1874	270	168
225/50ZR16	92W	500AA	8.0	10.1	630	1389	270	168
205/50ZR17	93W XL	500AA	8.0	10.1	650	1433	270	168
215/50ZR17	95W XL	500AA	8.0	10.1	690	1521	270	168
225/50ZR17	98W XL	500AA	8.0	10.1	750	1653	270	168
225/50ZR18	99W XL	500AA	8.0	10.1	775	1709	270	168
235/50ZR18	101W XL	500AA	8.0	10.1	825	1819	270	168
205/45ZR17	88W XL	500AA	8.0	10.1	560	1235	270	168
215/45ZR17	91W XL	500AA	8.0	10.1	615	1356	270	168
225/45ZR17	94W XL	500AA	8.0	10.1	670	1477	270	168
235/45ZR17	97W XL	500AA	8.0	10.1	730	1609	270	168
245/45ZR17	99W XL	500AA	8.0	10.1	775	1709	270	168
215/45ZR18	93W XL	500AA	8.0	10.1	650	1433	270	168
225/45ZR18	95W XL	500AA	8.0	10.1	690	1521	270	168
235/45ZR18	98W XL	500AA	8.0	10.1	750	1653	270	168
245/45ZR18	100W XL	500AA	8.0	10.1	800	1764	270	168
245/45ZR19	102W XL	500AA	8.0	10.1	850	1874	270	168
205/40ZR17	84W XL	500AA	8.0	10.1	500	1102	270	168
215/40ZR18	89W XL	500AA	8.0	10.1	580	1279	270	168
225/40ZR18	92W XL	500AA	8.0	10.1	630	1389	270	168
235/40ZR18	97W XL	500AA	8.0	10.1	730	1609	270	168
245/40ZR18	97W XL	500AA	8.0	10.1	730	1609	270	168
235/40ZR19	96W XL	500AA	8.0	10.1	710	1565	270	168
245/40ZR19	98W XL	500AA	8.0	10.1	750	1653	270	168
265/35ZR18	97W XL	500AA	8.0	10.1	730	1609	270	168
245/35ZR19	97W XL	500AA	8.0	10.1	730	1609	270	168
225/35ZR20	93W XL	500AA	8.0	10.1	650	1433	270	168
245/35ZR20	95W XL	500AA	8.0	10.1	690	1521	270	168
255/35ZR20	97W XL	500AA	8.0	10.1	730	1609	270	168
285/30ZR19	98Y XL	500AA	8.0	10.1	750	1635	300	186
275/30ZR20	97W XL	500AA	8.0	10.1	730	1609	270	168



## ETALON

CUV



- Etalon gives you the all weather handling you need for your crossover vehicle, while delivering a comfortable and quiet ride.
- Circumferential zigzag grooves resist hydroplaning by channeling water away from the tread grooves.
- Optimized tread profile design reduces rolling resistance heavily and increases fuel efficiency.
- Integrated shoulder minimizes road noise and uneven wear for quite ride.



Size	LI/SI	UTQG	TD mm	32nds	Load Capacity kg	Load Capacity lbs	Max.Speed Km/h	Max.Speed mph
235/75R15	105H	500AA	8.3	10.5	925	2039	210	130
215/70R16	100H	500AA	8.0	10.1	800	1764	210	130
225/70R16	103H	500AA	8.0	10.1	875	1929	210	130
235/70R16	106H	500AA	8.0	10.1	950	2094	210	130
245/70R16	111T XL	500AA	8.0	10.1	1090	2403	190	118
255/70R16	111T	500AA	8.3	10.5	1090	2403	190	118
265/70R16	112T	500AA	8.3	10.5	1120	2469	190	118
245/70R17	100T (110 T)	500AA	8.3	10.5	800	1764	190	118
265/70R17	115S	500AA	8.3	10.5	1215	2679	180	112
235/65R16	103H	500AA	8.0	10.1	875	1929	210	130
215/65R17	99H	500AA	8.0	10.1	775	1709	210	130
225/65R17	102H	500AA	8.0	10.1	850	1875	210	130
235/65R17	108V XL	500AA	8.0	10.1	1000	2205	240	149
245/65R17	111H XL	500AA	8.0	10.1	1090	2406	210	130
265/65R17	112H	500AA	8.0	10.1	1120	2469	210	130
235/65R18	110H XL	500AA	8.0	10.1	1060	2337	210	130
265/65R18	114H	500AA	8.0	10.1	1180	2601	210	130
275/65R18	116H	500AA	8.0	10.1	1250	2756	210	130
215/60R17	96H	500AA	8.0	10.1	710	1565	210	130
225/60R17	99V	500AA	8.3	10.5	775	1709	240	149
235/60R17	103S XL (106V XL)	500AA	8.3	10.5	875	1929	180	112
235/60R18	107V XL	500AA	8.0	10.1	975	2149	240	149
265/60R18	110V	500AA	8.0	10.1	1060	2337	240	149
235/55R18	100V	500AA	8.0	10.1	800	1764	240	149
255/55R18	109V XL	500AA	8.0	10.1	1030	2271	240	149



# IMPERO

SUV



- 4 wide longitudinal grooves improves drainage performance.
- Anti-hydroplaning lateral grooves offers excellent wet performance.
- 3 center block provide straight-driving stability.
- Optimized shoulder blocks maximize grip during cornering.



Size	LI/SI	UTQG	TD mm	32nds	Load Capacity kg	Load Capacity lbs	Max.Speed Km/h	Max.Speed mph
235/55ZR19	105W XL	500AA	8.0	10.1	905	2039	270	168
255/55R19	111V XL	500AA	8.0	10.1	1090	2403	240	149
235/55ZR20	105W XL	500AA	8.0	10.1	905	2039	270	168
275/55ZR20	117W XL	500AA	8.3	10.5	1285	2833	270	168
275/50R22	115H XL	500AA	8.3	10.5	1215	2679	210	130
245/45ZR20	103W XL	500AA	8.0	10.1	875	1929	270	168
255/45ZR20	105W XL	500AA	8.0	10.1	925	2039	270	168
275/45R20	110V XL	500AA	8.3	10.5	1060	2337	240	149
285/45R22	114V XL	500AA	8.3	10.5	1180	2601	240	149
305/45R22	118V XL	500AA	8.3	10.5	1320	2910	240	149
275/40ZR20	106W XL	500AA	8.3	10.5	950	2094	270	168
305/40R22	114V XL	500AA	8.3	10.5	1180	2601	240	149
265/40ZR22	106W XL	500AA	8.3	10.5	950	2094	270	168
285/40ZR22	110Y XL	500AA	8.3	10.5	1060	2337	300	186
275/35ZR20	102Y XL	500AA	8.0	10.1	850	1874	300	186
265/35ZR22	102W XL	500AA	8.0	10.1	850	1875	270	168
285/35ZR22	106W XL	500AA	8.3	10.5	950	2094	270	168
275/35ZR24	106W XL	500AA	8.0	10.1	950	2094	270	168
295/35R24	110V XL	500AA	8.0	10.1	1060	2337	240	149
305/35ZR24	112W XL	500AA	8.3	10.5	1120	2469	270	168
315/35ZR20	110W XL	500AA	8.3	10.5	1060	2337	270	168
235/30ZR22	90W XL	500AA	8.3	10.5	600	1323	270	168
245/30ZR22	95W XL	500AA	8.0	10.1	690	1521	270	168
255/30ZR24	97W XL	500AA	8.0	10.1	730	1609	270	168
295/25ZR22	97W XL	500AA	8.0	10.1	730	1609	270	168

# ARTORIA EV

EV SERIAL TIRE





## ARTORIA EV

EV



- Brand-New Silent pattern Technology, three kinds of computer-optimized varying pitch sequence combined with highly elastic tread formulation idea.
- Adopts super rigidity block for tread central pattern, which not only meets the requirements of high wear mileage, but also provides excellent grip, effectively transferring the huge torque of e-vehicle, and obtains high-speed stability.
- Perfect high bearing capacity. Introduce high load, high safety multiple structure design, to avoid stress concentration, meanwhile optimized each material plus improved liner formulation.
- Tread pattern with high rigid pattern block and high void ratio design, with ultra-low roll resistance formula design, effectively reduce the tire internal energy loss during driving process, so as to reduce rolling energy consumption, improve the endurance mileage of electric vehicles.
- New composite tread material design, creative tread mouth arrangement, upgraded design of crown band layer to strongly guarantee ultra-low rolling resistance.



Size	LI/SI	UTQG	TD mm	32nds	Load Capacity kg	Load Capacity lbs	Max.Speed Km/h	Max.Speed mph
235/45ZR18	98Y XL	380AA	7.0	8.8	750	1653	300	186
255/45ZR19	104Y XL	380AA	7.0	8.8	900	1984	300	186
235/40ZR19	96W XL	380AA	7.0	8.8	710	1565	270	168
285/40ZR19	107Y XL	380AA	7.0	8.8	975	2149	300	186
255/40ZR20	101Y XL	380AA	7.0	8.8	825	1819	300	186



## CONSENZO H/T HT



- 3D wave-patterned kerfs design used in tires provide improved grip and handling performance by minimizing block movement when driving, heavily improved all season performance.
- Multi-depth lateral lugs provide improved performance in wet and snow conditions.
- 4 straight grooves channel provides sure-footed performance in both wet and dry conditions.
- High stiffness center block improves steering performance.
- Button elements sized for good snow and wet traction, yet interlocking geometry maintains rib stiffness for handling.



Size	LI/SI	UTQG	TD	Load Capacity	DUAL LOAD	Max.Speed				
			mm	32nds	kg	lbs	kg	lbs	Km/h	mph
LT215/85R16-10PR	115/112 S	/	9.9	12.5	1215	2680	1120	2470	180	112
LT235/85R16-10PR	120/116 Q	/	9.9	12.5	1380	3042	1260	2778	160	99
LT235/80R17-10PR	120/117 Q	/	9.9	12.5	1400	3085	1285	2835	160	99
LT225/75R16-10PR	115/112 S	/	9.9	12.5	1215	2680	1120	2470	180	112
LT245/75R16-10PR	120/116 S	/	10.7	13.5	1400	3042	1260	2778	180	112
LT265/75R16-10PR	123/120 Q	/	10.7	13.5	1550	3415	1400	3085	160	99
LT245/75R17-10PR	121/118 Q	/	10.7	13.5	1450	3195	1320	2910	160	99
LT245/70R17-10PR	119/116 S	/	10.7	13.5	1360	3000	1250	2755	180	112
LT265/70R17-10PR	121/118 Q	/	10.7	13.5	1450	3195	1320	2910	160	99
235/75R15	109H	500AA	8.2	10.3	1030	2271	/	/	210	130
215/70R16	100H	500AA	8.2	10.3	800	1764	/	/	210	130
225/70R16	103T	500AA	8.2	10.3	875	1929	/	/	190	118
235/70R16	106H	500AA	8.2	10.3	950	2094	/	/	210	130
245/70R16	107H	500AA	8.2	10.3	975	2149	/	/	210	130
255/70R16	111H	500AA	8.2	10.3	1090	2403	/	/	210	130
265/70R16	112H	500AA	8.2	10.3	1120	2469	/	/	210	130
255/65R18	111H	500AA	8.5	10.7	1090	2403	/	/	210	130
245/60R18	105H	500AA	8.5	10.7	925	2039	/	/	210	130
275/60R20	114T	500AA	11.5	14.5	1180	2601	/	/	190	118
255/55R20	107V	500AA	9.5	12.0	975	2149	/	/	240	149
275/55R20	117H	500AA	11.5	14.5	1285	2833	/	/	210	130
245/50R20	102H	500AA	9.5	12.0	850	1874	/	/	210	130
255/50R20	109V XL	500AA	9.5	12.0	1030	2271	/	/	240	149
265/50R20	107H	500AA	9.5	12.0	975	2149	/	/	210	130



## IMPERO A/T AT



- Wraparound tread gives tires a rugged look and guards against cuts, bruises and impact breaks, affords outstanding traction especially in muddy or snowy conditions.
- Reinforced wide tread gauge helps to prevent internal damage from impacts sustained when off the road.
- Thick sidewall rubber gauge helps to minimize damage from off-road impact.
- Reinforced carcass and rubber gauge improved hill climbing and steering stability both on and off the road.



Size	LI/SI	UTQG	TD mm	32nds	Load Capacity		DUAL LOAD kg	Lbs	Max.Speed Km/h	Max.Speed mph
					kg	lbs				
215/75R15	100T	600AA	9.6	12.1	800	1764	/	/	190	118
255/70R15	108S	600AA	10.4	13.1	1000	2205	/	/	180	112
265/70R15	112S	600AA	10.4	13.1	1120	2469	/	/	180	112
245/70R16	107H	600AA	10.4	13.1	975	2149	/	/	210	130
265/65R17	112T	600AA	10.4	13.1	1120	2469	/	/	190	118
275/60R20	119H XL	600AA	10.4	13.1	1360	2998	/	/	210	130
275/55R20	117H XL	600AA	10.4	13.1	1285	2833	/	/	210	130
31*10.50R15LT-6PR	109S	/	12.8	16.1	1030	2271	/	/	180	112
35*12.50R20LT-12PR	126R	/	12.2	15.4	1700	3750	/	/	170	106
33*12.50R22LT-12PR	123S	/	12.2	15.4	1550	3415	/	/	170	106
35*12.50R22LT-12PR	126R	/	12.2	15.4	1700	3750	/	/	170	106
LT215/85R16-10PR	115/112 S	/	11.2	14.1	1215	2680	1120	2470	180	112
LT235/85R16-10PR	120/116 Q	/	11.2	14.1	1380	3042	1260	2778	160	99
LT235/80R17-10PR	120/117 S	/	11.2	14.1	1400	3085	1285	2835	180	112
LT235/75R15-8PR	110/107 S	/	11.2	14.1	1060	2335	975	2150	180	112
LT225/75R16-10PR	115/112 S	/	11.2	14.1	1215	2680	1120	2470	180	112
LT245/75R16-10PR	120/116 S	/	12.8	16.1	1400	3042	1260	2778	180	112
LT265/75R16-10PR	123/120 S	/	12.8	16.1	1550	3415	1400	3085	180	112
LT285/75R16-10PR	126/123 S	/	13.7	17.3	1700	3750	1550	3145	180	112
LT245/75R17-10PR	121/118 S	/	12.8	16.1	1450	3195	1320	2910	180	112
LT235/70R16-6PR	104/101 S	/	10.9	13.7	900	1984	825	1819	180	112
LT265/70R16-10PR	121/118 S	/	12.5	15.7	1450	3195	1320	2910	180	112
LT245/70R17-10PR	119/116 S	/	12.8	16.1	1360	3000	1250	2755	180	112
LT265/70R17-10PR	121/118 S	/	12.8	16.1	1450	3195	1320	2910	180	112
LT285/70R17-10PR	121/118 Q	/	13.7	17.3	1450	3195	1320	2910	160	99
LT265/70R18-10PR	124/121 S	/	12.8	16.1	1600	3525	1450	3195	180	112
LT275/70R18-10PR	125/122 S	/	12.8	16.1	1650	3460	1500	3305	180	112
LT275/65R18-10PR	123/120 S	/	12.8	16.1	1550	3415	1400	3085	180	112
LT285/65R18-10PR	125/122 R	/	12.2	15.4	1650	3640	1500	3305	170	106
LT325/65R18-10PR	127/124 S	/	12.2	15.4	1750	3860	1600	3525	180	112
LT275/65R20-10PR	126/123 S	/	12.8	16.1	1700	3750	1550	3415	180	112
LT265/60R20-10PR	121/118 S	/	12.8	16.1	1450	3195	1320	2910	180	112
LT285/60R20-10PR	125/122 S	/	13.7	17.3	1650	3640	1500	3305	180	112
LT325/60R20-10PR	126/123 S	/	12.2	15.4	1700	3750	1550	3415	180	112
LT265/50R20-10PR	121/118 S	/	12.2	15.4	1450	3195	1320	2910	180	112
LT275/55R20-10PR	120/117 S	/	12.2	15.4	1400	3085	1285	2833	180	112
LT285/55R20-10PR	122/119 S	/	12.2	15.4	1500	3305	1360	3000	180	112
LT305/55R20-10PR	121/118 S	/	12.2	15.4	1450	3195	1320	2910	180	112

# PANTHER CLAW R/IT

On/Off-The-Road





## PANTHER CLAW R/T RT



- Technologically advanced computer modeling for optimized tread pitch variation, perfectly placed tread sipes, and tread block alignment greatly reduce noise, providing a more civilized, comfortable, smooth, quiet ride.
- The sidewalls of the rogueblazer are equipped with three layers of polyester cord fabric and high-strength steel belts to combat sharp debris and rock.
- Enhanced fatigue resistant tread compound protects tire from chips/cuts/rocks/other debris, ensuring long life of tire by preventing early failure due to off-road use.
- Ultra-stable shoulder technology, the shifting shapes of the large shoulder blocks are designed for improved handling and control through dirt, mud, sand and snow.



Size	LI/SI	UTQG	TD	Load Capacity	DUAL LOAD	Max.Speed				
			mm	32nds	kg	lbs	kg	lbs	Km/h	mph
LT235/80R17-10/12PR	120/117 Q	/	13.0	16.4	1400	3085	1285	2835	160	99
LT285/70R17-10PR	121/118 Q	/	15.5	19.5	1450	3195	1320	2910	160	99
LT275/70R18-10PR	125/122 Q	/	14.5	18.3	1550	3415	1400	3085	160	99
LT275/65R18-10PR	123/120 Q	/	14.5	18.3	1550	3415	1400	3085	160	99
LT275/65R20-10PR	126/123 R	/	14.5	18.3	1700	3750	1550	3415	170	106
LT265/60R20-10PR	121/118 Q	/	13.5	17.0	1450	3195	1320	2910	160	99
LT275/55R20-10PR	120/117 Q	/	14.5	18.3	1400	3085	1285	2835	160	99
LT285/55R20-12PR	122/119 Q	/	14.5	18.3	1500	3305	1360	3000	160	99
33X12.50R17LT-12PR	121Q	/	15.5	19.5	1450	3195	/	/	160	99
35X12.50R17LT-12PR	121Q	/	15.7	19.8	1450	3195	/	/	160	99
33X12.50R18LT-12PR	122Q	/	15.7	19.8	1500	3305	/	/	160	99
35X12.50R18LT-12PR	128Q	/	15.7	19.8	1800	3970	/	/	160	99
33X12.50R20LT-12PR	119Q	/	15.4	19.4	1360	3000	/	/	160	99
35X12.50R20LT-12PR	126Q	/	15.7	19.8	1700	3750	/	/	160	99
33X12.50R22LT-12PR	114Q	/	15.5	19.5	1180	2600	/	/	160	99
35X12.50R22LT-12PR	121Q	/	15.5	19.5	1450	3195	/	/	160	99



## IMPERO M/T

MT



- Specially designed tread block provide better grip in mud, sand and snow.
- Unique Stone-ejector grooves along with a rugged shoulder help to prevent damage from impact.
- Optimized void-to-rubber ratio provides excellent traction.
- Large surface area tread blocks provide increased grip.



Size	LI/SI	UTQG	TD	Load Capacity	Max.Speed			
			mm	32nds	kg	lbs	Km/h	mph
33X12.50R15LT-6pr	108Q	/	15.7	19.8	1000	2205	160	99
33x12.50R18LT-10pr	118Q	/	15.7	19.8	1320	2910	160	99
33x12.50R20LT-10pr	114Q	/	15.4	19.4	1180	2600	160	99
35X12.50R15LT-6pr	113Q	/	15.7	19.8	1150	2535	160	99
35X12.50R17LT-10pr	121Q	/	15.7	19.8	1450	3195	160	99
35X12.50R18LT-10pr	123Q	/	15.7	19.8	1550	3415	160	99
35X12.50R20LT-10pr	121Q	/	15.7	19.8	1450	3195	160	99
LT285/65R18-10pr	125/122 Q	/	15.7	19.8	1650	3460	160	99

# CITY TRANS



Commercial Van

**CITY TRANS****VAN**

- New generation with high void ratio design, better pressure resistance, and deep zigzag pattern groove with good wear resistance.
- More full siping design help maintain wet traction, effectively conducts water away faster from the contact area.
- All-season performance and handling. The continuous zigzag middle 4-rib design improves straight line stability and turning maneuverability.



Size	LI/SI	UTQG	TD mm	32nds	Load Capacity kg	Load Capacity lbs	DUAL LOAD kg	DUAL LOAD lbs	Max.Speed Km/h	Max.Speed mph
195/75R16C-10PR	110/108 R	/	8.8	11.1	1060	2335	1000	2205	170	106
185/60R15C-8PR	94/92 T	/	8.8	11.1	670	1475	630	1390	190	118
235/65R16C-12PR	121/119 R	/	8.8	11.1	1450	3195	1360	3000	170	106